

Canon Projector Range Chart



XEED Models
Offer the highest image quality



Model	Short Throw Models		Compact Installation Models		Installation Models				
	XEED WUX450ST	XEED WUX500ST	XEED WUX500	XEED WUX6010	XEED WUX6500	XEED 4K500ST	XEED 4K501ST	XEED 4K600STZ	XEED 4K600Z
Positioning	Compact WUXGA short throw installation projector with lens shift.	Compact WUXGA short throw installation projector with lens shift.	Compact, high performance installation projector with versatile connections.	Canon's flagship WUXGA resolution installation projector with high brightness, lens options and HDBaset.	Canon's flagship WUXGA resolution installation projector with high brightness, lens options and HDBaset.	Enjoy next-generation image quality and flexibility with Canon's small, light, native 4K installation projectors.		Superior colour quality with today's smallest native 4K laser phosphor, LCOS installation projectors.	Bright, compact 4K laser phosphor projector with a standard lens for superior quality image reproduction.
Highlights	<ul style="list-style-type: none"> 1 WUXGA, 4500 lumens 2 0-75% Vertical lens shift 3 HDBaseT 4 PC-free multi projection 5 Wi-Fi 	<ul style="list-style-type: none"> 1 WUXGA, 5000 lumens 2 0-75% Vertical lens shift 3 HDBaseT 4 PC-free multi projection 5 Wi-Fi 	<ul style="list-style-type: none"> 1 WUXGA, 5000 lumens 2 Constant Brightness 3 HDBaseT 4 PC-free multi projection 5 Wi-Fi 	<ul style="list-style-type: none"> 1 WUXGA, 6000 lumens 2 Motorised lens shift, zoom & focus 3 Lens options 4 NMPJ 	<ul style="list-style-type: none"> 1 WUXGA, 6500 lumens 2 Motorised lens shift, zoom & focus 3 Lens options 4 NMPJ 	<ul style="list-style-type: none"> 1 Native 4K, 5000 lumens 2 Vertical lens shift +/- 60% 3 Edge blending 4 HDBaseT 5 Advanced registration 		<ul style="list-style-type: none"> 1 Native 4K, 6000 lumens 2 Edge blending 3 Marginal focus 4 Advanced registration 5 Control & error reporting via Wi-Fi** 	<ul style="list-style-type: none"> 1 Native 4K, 6000 lumens 2 Edge blending 3 Marginal focus 4 Advanced registration 5 Control & error reporting via Wi-Fi**
Panel type	3 x LCOS panels	3 x LCOS panels	3 x LCOS panels	3 x LCOS panels	3 x LCOS panels	3 x 4K-LCOS panels		3 x 4K LCOS panels	3 x 4K LCOS panels
Resolution	1920 x 1200 (WUXGA)	1920 x 1200 (WUXGA)	1920 x 1200 (WUXGA)	1920 x 1200 (WUXGA)	1920 x 1200 (WUXGA)	4096 x 2400 (4K)		4096 x 2400 (4K)	4096 x 2400 (4K)
Aspect ratio	16:10	16:10	16:10	16:10	16:10	approx.17:10 (128:75)		approx.17:10 (128:75)	approx.17:10 (128:75)
Brightness (lumens)	4500 / 3460 (Eco mode)	5000 (normal) / 3460 (eco)	5000 / 3800 (Eco mode)	6000 / 4660 (Eco mode)	6500 / 5270 (Eco mode)	5000 / 3750 (Eco mode)		6000 / 4560 (Quiet 1) / 2400 (Quiet 2)	6000 / 4560 (Quiet 1) / 2400 (Quiet 2)
Colour Brightness (lumens)	4500 / 3460 (Eco mode)	5000 (normal) / 3460 (eco)	5000 / 3800 (Eco mode)	6000 / 4660 (Eco mode)	6500 / 5270 (Eco mode)	5000 / 3750 (Eco mode)		6000 / 4560 (Quiet 1) / 2400 (Quiet 2)	6000 / 4560 (Quiet 1) / 2400 (Quiet 2)
Native Contrast Ratio	2000:1	2000:1	2000:1	2000:1	2000:1	3000:1		4000:1 (10,000:1 Dynamic)	4000:1 (10,000:1 Dynamic)
Zoom magnification and control	1.0x optical (fixed) / 12x digital	1.0x optical (fixed) / 12x digital	1.8x Manual	1.5x motorised (with standard lens)	1.5x motorised (with standard lens)	1.3x motorised		1.3x motorised	1.76x motorised
Throw ratio (100" type)	0.56:1	0.56:1	1.39 - 2.51:1	1.49-2.24:1 (with standard lens)	1.49-2.24:1 (with standard lens)	1.02 - 1.32:1		1.0 - 1.31:1	1.34 - 2.35:1
Projection distance coverage	0.35m - 3.64m	0.35m - 3.64m	1.2m - 16.2m	1.3m - 89m (Depending on lens)	1.3m - 89m (Depending on lens)	0.9m - 17.7m		1.2m - 30.9m	1.2m - 30.9m
Distance for 100" image	1.2m	1.2m	3.0m - 5.4m	3.2m - 4.8m (with standard lens)	3.2m - 4.8m (with standard lens)	2.2m - 2.9m		2.2m - 2.9m	2.9m - 5.2m
Screen size	30" - 300" (65 x 40cm - 646 x 404cm)	30" - 300" (65 x 40cm - 646 x 404cm)	40" - 300" (86 x 54cm - 646 x 404cm)	40" - 300" (86 x 54cm - 1292 x 808cm)	40" - 300" (86 x 54cm - 1292 x 808cm)	1.0m - 15.0m (40" - 600")		1.0m - 15.0m (40" - 600")	1.0m - 15.0m (40" - 600")
Keystone correction	H & V: +/- 12° Manual	H & V: +/- 12° Manual	H & V: +/- 20° Manual	H & V: +/- 20° Manual	H & V: +/- 20° Manual	H & V: +/- 20° Manual		H & V: +/- 20° Manual	H & V: +/- 20° Manual
Lens shift	Manual: V: 0-75%, H: +/-10%	Manual: V: 0-75%, H: +/-10%	Manual: V: 0-60%, H: +/-10%	Motorised: depends on lens	Motorised: depends on lens	Motorised: V: +/-60%, H: +/-10%		Motorised: V: +/-60%, H: +/-10%	Motorised: V: +/-60%, H: +/-10%
Digital video input	HDMI (supports DeepColour)	HDMI (supports DeepColour)	HDMI (supports DeepColour)	HDMI (supports DeepColour)	HDMI (supports DeepColour)	2 X HDMI (HDCP 1.4)	2 X HDMI (HDCP 2.2)	2 x HDMI* (HDCP 2.2)	2 x HDMI* (HDCP 2.2)
Digital RGB input	DVI-I 29-pin	DVI-I 29-pin	DVI-I 29-pin	DVI-I 29-pin	DVI-I 29-pin	4 x DVI-D 25-pin		4 x DVI-D 25-pin	4 x DVI-D 25-pin
Analogue RGB input	Mini D-Sub 15-pin	Mini D-Sub 15-pin	Mini D-Sub 15-pin	Mini D-Sub 15-pin	Mini D-Sub 15-pin	-		-	-
Component video input	Via adapter cable (optional)	Via adapter cable (optional)	Via adaptor cable (optional)	Via adapter cable (optional)	Via adapter cable (optional)	-		-	-
HDBaseT input	RJ-45	RJ-45	RJ-45	RJ-45	RJ-45	-		-	-
Wi-Fi connectivity	IEEE 802.11b/11g/11n	IEEE 802.11b/11g/11n	IEEE 802.11b/11g/11n	-	-	-		IEE 802.11b/11g/11n**	IEE 802.11b/11g/11n**
Audio input	2x 3.5mm mini-jack	2x 3.5mm mini-jack	2 x 3.5mm mini-jack	2x 3.5mm mini-jack	2x 3.5mm mini-jack	3.5mm mini-jack		3.5mm mini-jack	3.5mm mini-jack
Audio output	3.5mm mini-jack (variable level)	3.5mm mini-jack (variable level)	3.5mm mini-jack (variable level)	3.5mm mini-jack (variable level)	3.5mm mini-jack (variable level)	3.5mm mini-jack (variable level)		3.5mm mini-jack (variable output)	3.5mm mini-jack (variable output)
Network port	RJ-45 / HDBaseT	RJ-45 / HDBaseT	RJ-45 / HDBaseT	RJ-45 / HDBaseT	RJ-45 / HDBaseT	RJ-45		RJ-45	RJ-45
Service port / projector control	RS-232C, USB Type A, RJ-45	RS-232C, USB Type A, RJ-45	RS-232C, USB Type A, RJ-45	RS-232C, USB Type A, RJ-45	RS-232C, USB Type A, RJ-45	RS-232C, USB Type A, RJ-45		RS232C, USB Type A, RJ-45	RS232C, USB Type A, RJ-45
Direct power ON / OFF	Yes	Yes	Yes	Yes	Yes	Yes		Yes	Yes
Built-in speaker	5W	5W	5W	5W	5W	5W		5W	5W
Lamp life	Up to 3000h / 5000h (Eco mode)	Up to 3000h / 5000h (Eco mode)	Up to 3000h / 5000h (Eco mode)	Up to 3000h / 4000h (Eco mode)	Up to 3000h / 4000h (Eco mode)	Up to 3000h / 4000h (Eco mode)		Up to 20,000h / 40,000 (Ultra-long life mode)	Up to 20,000h / 40,000 (Ultra-long life mode)
Noise level	Normal: 37dB Eco: 30dB	Normal: 38dB Eco: 30dB	Normal: 37dB Eco: 30dB	Normal: 40dB Eco: 36dB	Normal: 43dB Eco: 39dB	Normal: 39dB Eco: 34dB		Normal: 37dB Quiet 1: 32dB / Quiet 2: 29dB	Normal: 37dB Quiet 1: 32dB / Quiet 2: 29dB
Dimensions incl protrusions (W x H x D)	337 x 136 x 415mm	337 x 136 x 415mm	337 x 136 x 370mm	380 x 170 x 430mm	380 x 170 x 430mm	470mm x 175mm x 533.5mm		559mm x 201mm x 624mm	559mm x 201mm x 624mm
Weight	6.3kg	6.3kg	5.9kg	8.5kg (without lens)	8.5kg (without lens)	17.6kg 18kg		26Kg	26Kg
Accessories	Ceiling bracket RS-CL16: 1214C001AA Air filter RS-FL02: 8379B001AA Carry bag RS-CIBG01: 0039X528 Lamp RS-LP08: 8377B001AA Optional foot RS-FT01: 8380B001AA	Ceiling bracket RS-CL16: 1214C001AA Air filter RS-FL02: 8379B001AA Carry bag RS-CIBG01: 0039X528 Lamp RS-LP08: 8377B001AA Optional foot RS-FT01: 8380B001AA	Ceiling Bracket RS-CL14: 4969B001AA Air Filter RS-FL02: 8379B001AA Air Filter RS-FL01: 4971B001AA Top cover (dark grey) RS-TC01: 5471B001AA Lamp RS-LP09: 9963B001AA	Ceiling Bracket RS-CL11: 4969B001AA Air Filter RS-FL01: 4971B001AA Air Filter RS-FL01: 4971B001AA Top cover (dark grey) RS-TC01: 5471B001AA Lamp RS-LP09: 9963B001AA	Ceiling Bracket RS-CL11: 4969B001AA Air Filter RS-FL01: 4971B001AA Air Filter RS-FL01: 4971B001AA Top cover (dark grey) RS-TC01: 5471B001AA Lamp RS-LP09: 9963B001AA	Ceiling bracket RS-CL15: 0964C001AA Air Filter RS-FL03: 0963C001AA Lamp & air filter RS-LPI0F: 1286C001AA	Ceiling bracket RS-CL15: 0964C001AA Ceiling mount arm RS-CL17: 2133C001AA Air Filter RS-FL04: 2128C001AA		Ceiling bracket RS-CL15: 0964C001AA Ceiling mount arm RS-CL17: 2133C001AA Air Filter RS-FL04: 2128C001AA

All models available as a dedicated medical installation projector that offer DICOM 14 compliance (XEED 4K models have built in DICOM sim mode as standard)

*4K60P, HDR, BT2020, DeepColour
**A non Wi-Fi version is available

Lens options for XEED WUX6010 & XEED WUX6500

Standard zoom lens RS-IL01ST: 4966B001AA

Aperture	1.89 - 2.65
Focal length	23.0mm - 34.5mm
Throw ratio	1.49 - 2.24:1
Projection distance	1.3m - 29.0m
Distance for 100" image	3.2m - 4.8m
Vertical lens shift	-15% to 55%
Horizontal lens shift	-10% to 10%
Zoom	1.5x motorised
Weight	550g



Long Zoom lens RS-IL02LZ: 4967B001AB

Aperture	1.99 - 2.83
Focal length	34.0mm - 57.7mm
Throw ratio	2.19 - 3.74:1
Projection distance	1.9m - 48.5m
Distance for 100" image	4.7m - 8.0m
Vertical lens shift	-15% to 55%
Horizontal lens shift	-10% to 10%
Zoom	1.7x motorised
Weight	755g



LIMITED STOCK

Ultra-long zoom lens RS-IL04UL: 6064B001AA

Aperture	2.34 - 2.81
Focal length	53.6mm - 105.6mm
Throw ratio	3.55 - 6.94:1
Projection distance	4.6m - 89.0m
Distance for 100" image	7.6m - 14.9m
Vertical lens shift	-15% to 55%
Horizontal lens shift	-10% to 10%
Zoom	1.95x motorised
Weight	940g



Wide zoom lens RS-IL05WZ: 8168B001AA

Aperture	2.09 - 2.34
Focal length	15.6mm - 23.3mm
Throw ratio	1.00 - 1.50:1
Projection distance	0.9m - 19.5m
Distance for 100" image	2.2m - 3.2m
Vertical lens shift	-15% to 55%
Horizontal lens shift	-10% to 10%
Zoom	1.5x motorised
Weight	905g



Canon Projector Range Chart



XEED Models
Offer the highest image quality



Model	Installation Models					
	XEED WUX5800	XEED WUX6700	XEED WUX7500	XEED WUX5800Z	XEED WUX6600Z	XEED WUX7000Z
Positioning	Versatile installation projectors offering high resolution and brightness			Lcos laser projectors offering high brightness and accurate colour		
Highlights	<ul style="list-style-type: none"> 1 WUXGA, 5800 lumens 2 6 interchangeable motorised lenses 3 HDBaseT 4 Motorised Focus Control 5 Wi-Fi 	<ul style="list-style-type: none"> 1 WUXGA, 6700 lumens 2 6 interchangeable motorised lenses 3 HDBaseT 4 Motorised Focus Control 5 Wi-Fi 	<ul style="list-style-type: none"> 1 WUXGA, 7500 lumens 2 6 interchangeable motorised lenses 3 HDBaseT 4 Motorised Focus Control 5 Wi-Fi 	<ul style="list-style-type: none"> 2 20000 hours life 3 360° installation & portrait 4 24/7 operation 5 Scheduling function 	<ul style="list-style-type: none"> 2 20000 hours life 3 360° installation & portrait 4 24/7 operation 5 Scheduling function 	<ul style="list-style-type: none"> 2 20000 hours life 3 360° installation & portrait 4 24/7 operation 5 Scheduling function
Panel type	3 x LCOS panels	3 x LCOS panels	3 x LCOS panels	3 x LCOS panels	3 x LCOS panels	3 x LCOS panels
Resolution	1920 x 1200 (WUXGA), 2304000 pixels	1920 x 1200 (WUXGA), 2304000 pixels	1920 x 1200 (WUXGA), 2304000 pixels	1920 x 1200 (WUXGA), 2304000 pixels	1920 x 1200 (WUXGA), 2304000 pixels	1920 x 1200 (WUXGA), 2304000 pixels
Aspect ratio	16:10	16:10	16:10	16:10	16:10	16:10
Brightness (lumens)	5800 / 5200 / 4500	6700 / 5200 / 4500	7500 / 5200 / 4500	5800 / 4060 / 2900	6600 / 4620 / 3300	7000 / 4900 / 3500
Colour Brightness (lumens)	5800 / 5200 / 4500	6700 / 5200 / 4500	7500 / 5200 / 4500	5800 / 4060 / 2900	6600 / 4620 / 3300	7000 / 4900 / 3500
Contrast Ratio	2000:1 (full on / full off)	2000:1 (full on / full off)	2000:1 (full on / full off)	4000:1 (Iris close 9) Dynamic: 20,000:1	4000:1 (Iris close 9) Dynamic: 20,000:1	4000:1 (Iris close 9) Dynamic: 20,000:1
Zoom magnification and control	1.5x Motorised (Standard Lens)	1.5x Motorised (Standard Lens)	1.5x Motorised (Standard Lens)	1.5x Motorised (Standard Lens)	1.5x Motorised (Standard Lens)	1.5x Motorised (Standard Lens)
Throw ratio (100" type)	1.49:1 - 2.24:1 (Standard lens)	1.49:1 - 2.24:1 (Standard lens)	1.49:1 - 2.24:1 (Standard lens)	1.49:1 - 2.24:1 (Standard lens)	1.49:1 - 2.24:1 (Standard lens)	1.49:1 - 2.24:1 (Standard lens)
Projection distance coverage (Depending on lens)	0.44m - 89.0m	0.44m - 89.0m	0.44m - 89.0m	0.44m - 89.0m	0.44m - 89.0m	0.44m - 89.0m
Distance for 100" image	3.2 - 4.8 (Standard lens)	3.2 - 4.8 (Standard lens)	3.2 - 4.8 (Standard lens)	3.2 - 4.8 (Standard lens)	3.2 - 4.8 (Standard lens)	3.2 - 4.8 (Standard lens)
Screen size	40" - 600" (86 x 54cm - 1292 x 808cm Depending on lens)	40" - 600" (86 x 54cm - 1292 x 808cm Depending on lens)	40" - 600" (86 x 54cm - 1292 x 808cm Depending on lens)	40" - 600" (86 x 54cm - 1292 x 808cm Depending on lens)	40" - 600" (86 x 54cm - 1292 x 808cm Depending on lens)	40" - 600" (86 x 54cm - 1292 x 808cm Depending on lens)
Keystone correction	H & V: +/- 20°	H & V: +/- 20°	H & V: +/- 20°	H & V: +/- 20°	H & V: +/- 20°	H & V: +/- 20°
Lens shift	Motorised: V: -15% - +55%, (Standard lens) H: +/-10%, Motorised	Motorised: V: -15% - +55%, (Standard lens) H: +/-10%, Motorised	Motorised: V: -15% - +55%, (Standard lens) H: +/-10%, Motorised	Motorised: V: -15% - +55%, (Standard lens) H: +/-10%, Motorised	Motorised: V: -15% - +55%, (Standard lens) H: +/-10%, Motorised	Motorised: V: -15% - +55%, (Standard lens) H: +/-10%, Motorised
Digital video input	HDMI (incl Deep Colour), DisplayPort	HDMI (incl Deep Colour), DisplayPort	HDMI (incl Deep Colour), DisplayPort	HDMI (incl Deep Colour), DisplayPort	HDMI (incl Deep Colour), DisplayPort	HDMI (incl Deep Colour), DisplayPort
Digital RGB input	DVI-I 29-pin	DVI-I 29-pin	DVI-I 29-pin	DVI-I 29-pin	DVI-I 29-pin	DVI-I 29-pin
Analogue RGB input	Mini D-Sub 15-pin	Mini D-Sub 15-pin	Mini D-Sub 15-pin	Mini D-Sub 15-pin	Mini D-Sub 15-pin	Mini D-Sub 15-pin
Component video input	Via adapter cable	Via adapter cable	Via adapter cable	Via adapter cable (optional)	Via adapter cable (optional)	Via adapter cable (optional)
HDBaseT input	RJ-45	RJ-45	RJ-45	RJ-45	RJ-45	RJ-45
Wi-Fi connectivity	IEEE 802.11b / g / n	IEEE 802.11b / g / n	IEEE 802.11b / g / n	IEEE 802.11b / g / n	IEEE 802.11b / g / n	IEEE 802.11b / g / n
Audio input	3.5mm stereo mini-jack	3.5mm stereo mini-jack	3.5mm stereo mini-jack	3.5mm stereo mini-jack	3.5mm stereo mini-jack	3.5mm stereo mini-jack
Audio output	3.5mm stereo mini-jack (variable level)	3.5mm stereo mini-jack (variable level)	3.5mm stereo mini-jack (variable level)	3.5mm stereo mini-jack (variable level)	3.5mm stereo mini-jack (variable level)	3.5mm stereo mini-jack (variable level)
Network port	RJ-45 HDBaseT input (1000BASE-T / 100BASE-TX / 10BASE-T)	RJ-45 HDBaseT input (1000BASE-T / 100BASE-TX / 10BASE-T)	RJ-45 HDBaseT input (1000BASE-T / 100BASE-TX / 10BASE-T)	RJ-45 HDBaseT input (1000BASE-T / 100BASE-TX / 10BASE-T)	RJ-45 HDBaseT input (1000BASE-T / 100BASE-TX / 10BASE-T)	RJ-45 HDBaseT input (1000BASE-T / 100BASE-TX / 10BASE-T)
Service port / projector control	Mini D-Sub 9-pin	Mini D-Sub 9-pin	Mini D-Sub 9-pin	Mini D-Sub 9-pin	Mini D-Sub 9-pin	Mini D-Sub 9-pin
Built-in speaker	1W RMS, Monaural	1W RMS, Monaural	1W RMS, Monaural	1W RMS, Monaural	1W RMS, Monaural	1W RMS, Monaural
Lamp life	3500 / 4000 hours	3000 / 4000 hours	3000 / 4000 hours	20000 hours	20000 hours	20000 hours
Noise level	Normal: 35dB Power save 1: 29 dB Power save 2: 27 dB	Normal: 35dB Power save 1: 29 dB Power save 2: 27 dB	Normal: 35dB Power save 1: 29 dB Power save 2: 27 dB	Quiet 1: 32dB / Quiet 2: 29dB	Quiet 1: 32dB / Quiet 2: 29dB	Quiet 1: 32dB / Quiet 2: 29dB
Dimensions excluding protrusions (W x H x D)	480mm x 196mm x 515mm	480mm x 196mm x 515mm	480mm x 196mm x 515mm	480mm x 196mm x 545mm	480mm x 196mm x 545mm	480mm x 196mm x 545mm
Weight	13kg (without lens)	13kg (without lens)	13kg (without lens)	17kg (without lens)	17kg (without lens)	17kg (without lens)
Accessories	Lamp RS-LPI2: 2406C001AA Air Filter RS-FL05: 2407C001AA Remote Control Unit RS-RC07: 2408C001AA Wired Remote Control unit RS-RC05: 5750B001AA Ceiling Mounting Bracket RS-CL15: 0964C001AC Ceiling Attachment Arm RS-CL17 (needed with CL15 bracket): 2133C001AA Ceiling Pipe 400-600mm RS-CL08: 3096B001AA Ceiling Pipe 600-1000mm RS-CL09: 3097B001AA			Air Filter RS-FL05: 2407C001AA Remote Control Unit RS-RC07: 2408C001AA Wired Remote Control unit RS-RC05: 5750B001AA Ceiling Mounting Bracket RS-CL15: 0964C001AC Ceiling Attachment Arm RS-CL17 (needed with CL15 bracket): 2133C001AA Ceiling Pipe 400-600mm RS-CL08: 3096B001AA Ceiling Pipe 600-1000mm RS-CL09: 3097B001AA		

All models include DICOM sim mode that offer DICOM 14 compliance (not approved for diagnostic purposes)

Lens options for XEED WUX5800, XEED WUX6700, XEED WUX7500, XEED WUX5800Z, XEED WUX6600Z & XEED WUX7000Z

Ultra-wide lens RS-SL06UW: 2701C001AA Aperture 2.4 Focal length 8.39mm Throw ratio 0.54:1 Projection distance 0.45m - 3.51m Distance for 100" image 1.16m Vertical lens shift -15% to 75% Horizontal lens shift -30% to 30% Zoom Weight 1605g	
Wide Zoom lens RS-SL05WZ: 2509C001AA Aperture 2.09 - 2.34 Focal length 15.56mm - 23.34mm Throw ratio 1.0 - 1.50:1 Projection distance 0.86m - 19.52m Distance for 100" image 2.15m - 3.23m Vertical lens shift -15% to 55% Horizontal lens shift -10% to 10% Zoom 1.5x powered Weight 1065g	
Long zoom lens RS-SL02LZ: 2506C001AA Aperture 1.99 - 2.83 Focal length 34mm - 57.7mm Throw ratio 2.19 - 3.74:1 Projection distance 1.86m - 48.5m Distance for 100" image 4.72m - 8.05m Vertical lens shift -15% to 55% Horizontal lens shift -10% to 10% Zoom 1.7x powered Weight 925g	
Standard zoom lens RS-SL01ST: 2505C001AA Aperture 1.89 - 2.65 Focal length 23.0mm - 34.5mm Throw ratio 1.49 - 2.24:1 Projection distance 1.27m - 28.98m Distance for 100" image 3.21m - 4.82m Vertical lens shift -15% to 55% Horizontal lens shift -10% to 10% Zoom 1.5x powered Weight 725g	
Ultra-long zoom lens RS-SL04UL: 2508C001AA Aperture 2.34 - 2.81 Focal length 53.6mm - 105.6mm Throw ratio 3.55 - 6.94:1 Projection distance 4.64m - 89.02m Distance for 100" image 7.64m - 14.94m Vertical lens shift -15% to 55% Horizontal lens shift -10% to 10% Zoom 1.97x powered Weight 110g	
Short fixed lens RS-SL03WF: 2507C001AA Aperture 2 Focal length 12.8mm Throw ratio 0.80:1 Projection distance 0.69m - 5.17m Distance for 100" image 1.73m Vertical lens shift -11.3% to 11.3% Horizontal lens shift -4.6% to 4.6% Zoom Weight 1060g	